

Тип ленты	Ширина ленты	Разрывное усилие ленты (daN), (кг)	Используемая скоба	Разрывное усилие системы (daN), (кг)	Используемое натяжное устройство
CC 40	13 mm	300	CB-4	480	CT 20
CC 40	13 mm	300	CB-4S	510	CT 20
CC 40/2	13 mm	190	CB-4	325	CT 20
CC 40/2	13 mm	190	CB-4N	350	CT 20
CC 40/2	13 mm	190	CB-4S	375	CT 20
CC 50	16 mm	425	CB-5	680	CT 20
CC 50	16 mm	425	CB-5S	725	CT 20
CC50UF	16 mm	425	CB-5	680	CT 20
CC50UF	16 mm	425	CB-5S	725	CT 20
CC 50/2	16 mm	250	CB-5	425	CT 20
CC 50/2	16 mm	250	CB-5S	475	CT 20
CC 55	16 mm	550	CB-5	790	CT 20
CC 55	16 mm	550	CB-5S	880	CT 20
CC 55UF	16 mm	550	CB-5	790	CT 20
CC 55UF	16 mm	550	CB-5S	880	CT 20
CC 60	19 mm	475	CB-6	760	CT 20 / CT 32 PN
CC 60	19 mm	475	CB-6S	800	CT 20 / CT 32 PN
CC 60/2	19 mm	300	CB-6	510	CT 20 / CT 32 PN
CC 60/2	19 mm	300	CB-6S	570	CT 20 / CT 32 PN
CC 60UF	19 mm	475	CB-6	760	CT 20 / CT 32 PN
CC 60UF	19 mm	475	CB-6S	800	CT 20 / CT 32 PN
CC 65	19 mm	625	CB-6	900	CT 20 / CT 32 PN
CC 65	19 mm	625	CB-6S	1000	CT 20 / CT 32 PN
CC 65UF	19 mm	625	CB-6	900	CT 20 / CT 32 PN
CC 65UF	19 mm	625	CB-6S	1000	CT 20 / CT 32 PN
CC69	21 mm	900	CB-6XHD	1440	CT 20 / CT 32 PN
CC 85	25 mm	785	CB-8	1250	CT 40-2 / CT 32 PN
CC 85	25 mm	785	CB-8L	1175	CT 40-2 / CT 32 PN
CC 85/4	25 mm	625	CB-8	1060	CT 25 / CT 40-2 / CT 32 PN